

Product Group - Golden Flake
Health and Safety at Work Act 1974 COSHH Regulations 1988

APPEARANCE AND FORM	Golden brown free flowing flake								
LEGISLATION	Complies with the Feeding Stuffs Regulations 2000 Agriculture act 1970.								
PACKAGING	25kg bags								
TOXICITY	<table><tr><td>Ingestion</td><td>Not hazardous in small quantities, may cause nausea and sickness, seek medical attention if this occurs</td></tr><tr><td>Skin Contact</td><td>Mild irritation possible</td></tr><tr><td>Eye Contact</td><td>Mild irritation possible</td></tr><tr><td>Inhalation</td><td>May irritate respiratory membranes</td></tr></table> <p>Product has a free fatty acid content of approximately 85%.</p>	Ingestion	Not hazardous in small quantities, may cause nausea and sickness, seek medical attention if this occurs	Skin Contact	Mild irritation possible	Eye Contact	Mild irritation possible	Inhalation	May irritate respiratory membranes
Ingestion	Not hazardous in small quantities, may cause nausea and sickness, seek medical attention if this occurs								
Skin Contact	Mild irritation possible								
Eye Contact	Mild irritation possible								
Inhalation	May irritate respiratory membranes								
CORROSION PROPERTIES	Low pH(pH4-5 in liquid state) and high FFA level								
FIRE RISK	Product has a relatively high flash point (circa 200°C)								
EXPLOSIVE RISK	Dust explosion hazard when sufficient dust concentrations are present.								
HANDLING PROCEDURES	During handling, ventilation should be adequate to maintain airborne dust concentrations below 10mg/M ³ . Smoking should be prohibited when handling this product.								
PROTECTIVE CLOTHING	Respiratory protection: Dust mask required if total dust level exceeds 10mg/M ³ . For those with sensitive skin, gloves should be worn. Safety glasses should also be worn.								
STORAGE CONDITIONS	The material should be stored in cool, dry and well ventilated buildings. Whilst the product will not heat of its own accord, care should be taken to keep out of direct sunlight and at a maximum warehouse temperature of 35°C. Pallets should not be stacked more than two high and there should be a gap between pallets to allow for air circulation. If very hot conditions (over 35 °C) should persist, it is advisable to remove shrink wrapping and break down the pallets.								
FIRST AID REQUIREMENTS	<table><tr><td>Eyes</td><td>Irrigate with warm water, then flush eyes copious amounts of water, seek medical attention</td></tr><tr><td>Skin</td><td>Wash thoroughly and remove contaminated clothing, if irritation occurs seek medical attention.</td></tr><tr><td>Inhalation</td><td>Remove to fresh air, if breathing is difficult seek medical attention.</td></tr><tr><td>Ingestion</td><td>Give water to dilute and seek medical attention</td></tr></table>	Eyes	Irrigate with warm water, then flush eyes copious amounts of water, seek medical attention	Skin	Wash thoroughly and remove contaminated clothing, if irritation occurs seek medical attention.	Inhalation	Remove to fresh air, if breathing is difficult seek medical attention.	Ingestion	Give water to dilute and seek medical attention
Eyes	Irrigate with warm water, then flush eyes copious amounts of water, seek medical attention								
Skin	Wash thoroughly and remove contaminated clothing, if irritation occurs seek medical attention.								
Inhalation	Remove to fresh air, if breathing is difficult seek medical attention.								
Ingestion	Give water to dilute and seek medical attention								
ENVIRONMENTAL INFO	Toxic to marine life								
THRESHOLD LIMITS	WEL 10mg/m ³ (8 hours)								
DISPOSAL OF SPILLAGE'S & WASTE	Mechanically collect and remove material and wash area with water if required, extreme care must be taken to prevent effluent and wash water entering surface water.								



